

OGISTIC

STABULON B - STABULON E

ANTI-SLIP

CORRUGATED TIE-SHEETS



COMPOSITION

- ► Anti-slip coating (top side)
- ► Corrugated board B or E flute
- ► Anti-slip coating (bottom side)

QUALITY OF PRODUCT

- ► High non-slip properties
- ► Tear and puncture resistant to nails and damaged pallets
- Superior rigidity high compression resistance
- ▶ 100% recyclable
- ▶ ISO 14062 Eco-designed certified
- ► Tertiary packaging, indirect food contact

APPLICATION USE

- Stabilize any packaging format
- Manual and automated applications

PALLETIZATION

- ► Standard pallet sheet sizes. Custom sizes available.
- ▶ 330 sheets per skid Stabulon B flute
- ▶ 500 sheets per skid Stabulon E flute
- ► Available with cut corners

SPECIFICATION SHEET

Paper type	FSC recycled paper		Standards
Weight	400 g/sqm		ISO 536
	Stabulon on Stabulon	Stabulon on Paper	
Slide angle	≥ 50°	≥ 40°	NF Q 03-083
Static coefficient of friction	≥ 1,2	≥ 0,8	ISO 8295
Dynamic coefficient of friction	≥ 0,6	≥ 0,4	ISO 8295



TECHNICOAT

Solution

www.cgp-coating.com