

Static Shielding Bag_ANT010SSB

Features:


- Metal "Faraday cage" layer shields products from electric energy inside and prevents static build-up
- Four layer protection guards against charges inside and out
- Semi transparent for easy content identification
- Surface resistance of 10^{8} - $10^{11}\Omega$
- Conforms to MIL-PRF-81705D Type III, EIA 625, EIA 541, ANSI/ESD S-20.20
- · Custom sizes and print available on request
- Suitable for packing electronic products which are sensitive to static, eg PCB's, IC integrated circuit, CD driver, HD etc

Additional Notes:

We recommend that all of our static shielding bags be used within 2 years from the date of manufacture. Store this product in its original packaging in a climate-controlled environment where temperature ranges from 21°C -23°C and relative humidity is 45 - 50%.









Construction:

Our static shielding bags are constructed in four layers, consisting of a static dissipative polyester outer layer and a static dissipative polyethylene inner layer with a centre metallised shield layer.

Our bags are manufactured from industry approved polyester and polyethelene laminates. The polyester dielectric works with the metal layer to provide a Faraday effect, the metal layer preventing penetration from damaging electrostatic fields. The specially processed polyethelene keeps tribocharging to a minimum.

Configuration(s):

Our bags are available in custom sizes or in several industry standard sizes. Bags are offered in a 2-seal configuration and bottom fold, with our standard flexographically printed artwork. Please note any bags that are longer than 24" will have a 3rd seal along the bottom edge. Our bags can also be personalised with your company logo on any bespoke orders.

Standard Bag Artwork:

Our static shielding bags are produced with the following sample artwork as standard. For further information on bespoke/printed orders, please contact one of our sales team. Please note there is a MOQ of 20,000 bags on all printed bags.



Static Shielding Bag_ANT010SSB

Test Conditions:

The following results were taken under the following environmental test conditions: Temperature: 23°C / Humidity: 43%



Technical Parameters:

Item:	Test Standard:	Result:	
Film Composition	N/A	PET-AL/PP	
Film Thickness	Micron Meter	2.9mils-3.1mils	
Metal Layer Resistance	ASTM D257	<100 Ω/sq	
Metal Layer Optical Transmission	ASTM D1003	40% +/- 5% optical density	
Surface Resistivity	ASTM D257	<10 ¹⁰ Ω/sq	
Time for static removal	FTMS 101B Method 4046 - 5000-0V	<0.01 Sec	
Friction Static	E1A541 Appendix C Avg.	TriboelectricNanocolombs Quartz<13n/in Tefion.<13n/in	
Capacitance Release	E1A541 Voltage Difference	<10V	
Anti-erosion	FTMS 101C Method 3005	No visible spots	
Tensile Strength	ASTM D882	>18 lbs./in	
Tear Initiation	ASTM D1004	>2.5 lbs./in	
Puncture Resistance	ASTM D3420	>100 PSI	
Tear Resistance	ASTM D882	>8 lbs./in	
MVTR	ASTM E 96	<0.2 gm/100in-2/4hrs	
Oxygen Barrier	ASTM D 3985	<0.5 CC/100in-2/4hrs	
Heat Seal Temperature	-	250 - 375 °F	
Heat Seal Pressure	-	30-70 PSI	
Breaking Tensile Force	GB/96-04-10	N/15mm	
Breaking Elongation Rate	GB/96-04-10	%	
Laminating Strength	GB/96-04-10	N/15mm	
Seal Strength	GB/96-04-10	N/15mm	
Appearance	GB/96-04-10	No delamination, burst seal, wrinkle, warp, break, foreign particle adherence, air bubble beyond sealing $\phi \leq 3mm$	

Test Conclusion: (Date of Issue: 2009-11-10)

The shielding bag is tested accordance with the relevant test standard and requirements.

Test Item:	Test Method:	Measured Equipment(s):	MDL:
Lead (Pb)	IEC 62321:2008 Ed.1 Sec.8	ICP-OES	2mg/kg
Cadmium (Cd)	IEC 62321:2008 Ed.1 Sec.8	ICP-OES	2mg/kg
Mercury (Hg)	IEC 62321:2008 Ed.1 Sec.7	ICP-OES	2mg/kg
Hexavalent Chromium (Cr(VI))	IEC 62321:2008 Ed.1 Annex C	UV-Vis	2mg/kg
Polybrominated Biphenyls (PBBs)	IEC 62321:2008 Ed.1 Annex A	GC-MS	5mg/kg
Polybrominated Diphenyl Ethers (PBDEs)	IEC 62321:2008 Ed.1 Annex A	GC-MS	5mg/kg



Static Shielding Bag_ANT010SSB

Product Code:	Description:	Size (inches):	Size (mm):	Additional Notes:
010-0085	Static Shielding Bag	2 x 6	50.8 x 152	Pack of 100
010-0001	Static Shielding Bag	3 x 5	76 x 127	Pack of 100
010-0005	Static Shielding Bag	4 x 6	102 x 152	Pack of 100
010-0008	Static Shielding Bag	4 x 12	102 x 127	Pack of 100
010-0009	Static Shielding Bag	4 x 24	102 x 610	Pack of 100
010-0011	Static Shielding Bag	5 x 8	127 x 203	Pack of 100
010-0012	Static Shielding Bag	5 x 26	127 x 660.4	Pack of 100
010-0014	Static Shielding Bag	6 x 8	152 x 203	Pack of 100
010-0015	Static Shielding Bag	6 x 10	152 x 254	Pack of 100
010-0016	Static Shielding Bag	6 x 12	152 x 305	Pack of 100
010-0021	Static Shielding Bag	7 x 16	177.8 x 406	Pack of 100
010-0024	Static Shielding Bag	8 x 10	203 x 254	Pack of 100
010-0025	Static Shielding Bag	8 x 12	203 x 305	Pack of 100
010-0022	Static Shielding Bag	8 x 20	203 x 508	Pack of 100
010-0027	Static Shielding Bag	8 x 30	203 x 762	Pack of 100
010-0029	Static Shielding Bag	10 x 12	254 x 305	Pack of 100
010-0030	Static Shielding Bag	10 x 14	254 x 355	Pack of 100
010-0031	Static Shielding Bag	10 x 16	254 x 457	Pack of 100
010-0040	Static Shielding Bag	12 x 14	305 x 355	Pack of 100
010-0041	Static Shielding Bag	12 x 16	305 x 406	Pack of 100
010-0042	Static Shielding Bag	12 x 18	305 x 457	Pack of 100
010-0048	Static Shielding Bag	14 x 18	355 x 457	Pack of 100
010-0097	Static Shielding Bag	14 x 24	355 x 610	Pack of 100
010-0055	Static Shielding Bag	16 x 18	406 x 457	Pack of 100
010-0056	Static Shielding Bag	16 x 20	406 x 508	Pack of 100
010-0058	Static Shielding Bag	18 x 18	457 x 457	Pack of 100
010-0059	Static Shielding Bag	18 x 20	457 x 508	Pack of 100
010-0060	Static Shielding Bag	18 x 24	457 x 610	Pack of 100
010-0096	Static Shielding Bag	20 x 24	508 x 610	Pack of 100

Note: Other sizes available upon request.